



Configure your own Control Station

Area of information

ZONING

GAS 1 21

DUST 21 22

EXPLOSION GROUP

IIA IIB IIC

TEMPERATURE CLASS

T4 T5 T6

TEMPERATURE

AMBIENT °C - °C UP TO + °C

RATED VOLTAGE :

V

MODE OF PROTECTION :

EXD EXE EXI OTHER :

MATERIAL :

ALUMINUM STAINLESS STEEL GRP

NUMBER OF ACTIVATOR ON FRONT SIDE :

LEGEND		REQUIREMENTS		
		OPERATOR	COLOR	CONTACTS/POLES
1	PUSH BUTTON MOMENTARY			
2	PUSH BUTTON STEADY			
3	EMERGENCY P.B.			
4	2 POS. SELECTOR			
5	3 POS. SELECTOR			
6	KEY SELECTOR SWITCH			
7	PILOT LIGHT			
8	SPECIAL SELECTOR (PROVIDE DIAGRAM)			
9	METER : TO BE SPECIFIED			
10	OTHER : TO BE SPECIFIED			

WIRING :

YES NO (DIRECT WIRING)

ENTRY SPECIFICATION :

METRIC INCHES

SIZE	M20- 1/2"				M25 - 3/4"				M32 - 1"				M40 - 1 1/2"				M50 - 1 1/4"				M63 - 2"			
ENCLOSURE SIDE	A	B	C	D	A	B	C	D	A	B	C	D	A	B	C	D	A	B	C	D	A	B	C	D
POLY GLAND																								
METAL GLAND																								
ARMOURED GLAND																								
POLY PLUG																								

COMPLEMENTARY INFORMATION :

CONTACT DETAILS

REQUEST FOR QUOTATION

NAME : _____

COMPANY : _____

EMAIL ADDRESS : _____

ADDRESS : _____

REQUEST FOR SALES ENGINEER VISIT

PHONE NUMBER : _____

FAX NUMBER : _____

COMMENTS : _____
