



Lighting requirements

Area of information

ZONING

GAS 1 2

DUST 21 22

EXPLOSION GROUP

IIA IIB IIC

TEMPERATURE CLASS

T1 T2 T3 T4 T5 T6

TEMPERATURE

AMBIENT °C - °C UP TO + °C

RATED VOLTAGE :

VOLTAGE V FREQUENCY HZ

MODE OF PROTECTION :

EXD EXE OTHER :

MATERIAL :

ALUMINUM STAINLESS STEEL

TYPE OF LAMP :

FLUORESCENT SODIUM

METAL HALIDE MERCURY

HALOGEN LED

IP :

65 66 67

TYPE OF LIGHTING :

1 TUBE LANTERN/ WELLGLASS

2 TUBES FLOODLIGHT

POWER NEEDS : W

MOUNTING SUPPORT :

WALL CEILING POLE

EMERGENCY VERSION :

YES DURATION TIME 60 MIN 90 MIN 120 MIN

ENTRY SPECS :

Number of Entries

Size needed M20 M25 M32 M40

Armoured cable Yes No

Cable detail

CONTACT DETAILS

REQUEST FOR QUOTATION REQUEST FOR SALES ENGINEER VISIT

NAME : _____ PHONE NUMBER : _____

COMPANY : _____ FAX NUMBER : _____

EMAIL ADDRESS : _____ COMMENTS : _____

ADDRESS : _____
