



Configure your own Control Station

Area of information

ZONING	
GAS	1 21
DUST	21 22
EXPLOSION GROUP	
	IIA IIB IIC
TEMPERATURE CLASS	
	T4 T5 T6
TEMPERATURE	
AMBIENT	°C - °C UP TO + °C

RATED VOLTAGE:

MODE OF PROTECTION:

EXD EXE EXI OTHER:

MATERIAL:

ALUMINUM STAINLESS STEEL GRP

NUMBER OF ACTIVATOR ON FRONT SIDE:

LEGEND		REQUIREMENTS		
		OPERATOR	COLOR	CONTACTS/POLES
1	PUSH BUTTON MOMENTARY			
2	PUSH BUTTON STEADY			
3	EMERGENCY P.B.			
4	2 POS. SELECTOR			
5	3 POS. SELECTOR			
6	KEY SELECTOR SWITCH			
7	PILOT LIGHT			
8	SPECIAL SELECTOR (PROVIDE DIAGRAM)			
9	METER: TO BE SPECIFIED			
10	OTHER: TO BE SPECIFIED			

WIRING:

YES NO (DIRECT WIRING)

ENTRY SPECIFICATION:

METRIC INCHES

ENCLOSURE SIDE	TAILLE	M20- 1/2"				M25 - 3/4"				M32 - 1"				M40 -1 1/2"				M50 - 1 1/4"				M63 - 2"			
		A	B	C	D	A	B	C	D	A	B	C	D	A	B	C	D	A	B	C	D	A	B	C	D
POLY GLAND																									
METAL GLAND																									
ARMOURED GLAND																									
POLY PLUG																									

COMPLEMENTARY INFORMATION:

CABLE ARME OU NON _____
 TERRE TRAVERSANTE _____

CONTACT DETAILS:

REQUEST FOR QUOTATION	REQUEST FOR SALES ENGINEER VISIT
NAME: _____	PHONE NUMBER : _____
COMPANY: _____	FAX NUMBER : _____
EMAIL ADDRESS : _____	COMMENTS : _____
ADDRESS : _____	_____
_____	_____