



# Lighting requirements

## Area of information

### ZONING

GAS	1	2
DUST	21	22

### EXPLOSION GROUP

IIA	IIB	IIC
-----	-----	-----

### TEMPERATURE CLASS

T1	T2	T3	T4	T5	T6
----	----	----	----	----	----

### TEMPERATURE

AMBIENT	°C	-	°C	UP TO	+	°C
---------	----	---	----	-------	---	----

### RATED VOLTAGE:

VOLTAGE	V	FREQUENCY	HZ
---------	---	-----------	----

### MODE OF PROTECTION:

EXD	EXE	OTHER:
-----	-----	--------

### MATERIAL:

ALUMINIUM	STAINLESS STEEL
-----------	-----------------

### TYPE OF LAMP:

FLUORESCENT	SODIUM
METAL HALIDE	MERCURY
HALOGEN	LED

### IP:

65	66	67
----	----	----

### TYPE OF LIGHTING:

1 TUBE	LANTERN/ WELLGLASS
2 TUBES	FLOODLIGHT
POWER NEEDS:	LED lm
	W

### MOUNTING SUPPORT:

WALL	CEILLING	POLE
------	----------	------

### EMERGENCY VERSION:

YES	DURATION TIME	60 MIN	90 MIN	120 MIN	180 MIN
-----	---------------	--------	--------	---------	---------

### ENTRY SPECS:

Number of Entries				
Size needed	M20	M25	M32	M40
Armoured cable	Yes		No	
Cable detail				

### CONTACT DETAILS:

REQUEST FOR QUOTATION	REQUEST FOR SALES ENGINEER VISIT
NAME: _____	PHONE NUMBER : _____
COMPANY: _____	FAX NUMBER : _____
EMAIL ADDRESS : _____	COMMENTS : _____
ADDRESS : _____	_____
_____	_____