



Configure your own Control Station

Area of information

ZONING

GAS	1	2
DUST	21	22

EXPLOSION GROUP

	IIA	IIB	IIC
--	-----	-----	-----

TEMPERATURE CLASS

	T4	T5	T6
--	----	----	----

TEMPERATURE

AMBIENT	°C	-	°C	UP TO	+	°C
---------	----	---	----	-------	---	----

RATED VOLTAGE:

MODE OF PROTECTION:

EXD EXE EXI OTHER:

MATERIAL:

ALUMINUM STAINLESS STEEL GRP

NUMBER OF ACTIVATOR ON FRONT SIDE:

LEGEND

1	PUSH BUTTON MOMENTARY
2	PUSH BUTTON STEADY
3	EMERGENCY P.B.
4	2 POS. SELECTOR
5	3 POS. SELECTOR
6	KEY SELECTOR SWITCH
7	PILOT LIGHT
8	SPECIAL SELECTOR (PROVIDE DIAGRAM)
9	METER: TO BE SPECIFIED
10	OTHER: TO BE SPECIFIED

REQUIREMENTS

OPERATOR	COLOR	CONTACTS/POLES

WIRING:

YES NO (DIRECT WIRING)

ENTRY SPECIFICATION:

METRIC INCHES

ENCLOSURE SIDE	M20- 1/2"				M25 - 3/4"				M32 - 1"				M40 - 1 1/2"				M50 - 1 1/4"				M63 - 2"				A	B	C	D		
	A	B	C	D	A	B	C	D	A	B	C	D	A	B	C	D	A	B	C	D	A	B	C	D						
POLY GLAND																														
METAL GLAND																														
ARMOURED GLAND																														
POLY PLUG																														

COMPLEMENTARY INFORMATION:

CABLE ARME OU NON _____

TERRE TRAVERSANTE _____

CONTACT DETAILS:

REQUEST FOR QUOTATION

NAME: _____

COMPANY: _____

EMAIL ADDRESS : _____

ADDRESS : _____

REQUEST FOR SALES ENGINEER VISIT

PHONE NUMBER : _____

FAX NUMBER : _____

COMMENTS : _____
